

Colour Video Door Phone Kit with memory function



CTHCK7EM



Introducing a Premium Quality Color Video Door phone with 7" TFT Hands-free Monitor with built-in memory that stores up to 200 images. Surface Mount, vandal proof Outdoor Camera that gives clear colored images even at night & low light conditions.

Technical Specifications

Indoor Monitor	Model No - CTHCM7EM
Display	7" TFT - LCD
Video Input	1VP-P/75Ω
Audio SNR	>25dB
Audio Distortion	≤7%
Standby Current	≤60mA
Working Current	≤500mA
Operating Voltage	DC18V±10%
Operating Temperature	(-10)~(+55)°C
Installation	Surface Mount
Dimension (mm)	210 x 150 x 23(mm)
Outdoor Camera	Model No - CTHCC7E
Min. Illumination	0.1LUX
Lens	3.6 mm 92° angle
Light Sources	6 white LEDs
Video Output	1VP-P/75Ω
Audio SNR	>25dB
Audio Distortion	<5%
Standby Current	≤60mA
Working Current	≤230mA
Operating Voltage	DC18V±10%
Operating Temperature	(-40)~70°C
Operating Humidity	0 ~100%
Installation	Surface Mount
Dimension (mm)	79 x 148 x 45(mm)

Features

Indoor monitor has built-in memory to store up-to 200 images with date and time stamp

Hands-free Video Door Phone to call, monitor and release door Locks

Expandable up to 4 Indoor Monitors and 4 Outdoor Cameras

Call Transfer, Broadcasting and Intercom Facility between Indoor Monitors

Sleek and Elegant Design suitable for villas and apartments

Backlit Touch Buttons

Do Not Disturb option available. Mutes the call ringing from Outdoor Camera while only displaying the video

More than 10 melodies for ringtone selection

4 wire System, PLUG & PLAY connection, easy to install

6 White LED's on Outdoor Camera provides clear colored image at night

Connect and Operate all kinds of Electric Door locks

Vandal-proof Outdoor Camera Made of Cast-Aluminum

Backlit Name Tag and Call Button on Outdoor Camera

Colour Video Door Phone Kit



CTHCK7E



Introducing a Premium Quality Color Video Door phone with 7" TFT Hands-free Monitor & Surface Mount, vandal proof Outdoor Camera that gives clear colored images even at night & low light conditions.

Technical Specifications

Indoor Monitor	Model No - CTHCM7E
Display	7" TFT - LCD
Video Input	1VP-P/75Ω
Audio SNR	>25dB
Audio Distortion	≤7%
Standby Current	≤60mA
Working Current	≤500mA
Operating Voltage	DC18V±10%
Operating Temperature	(-10)~(+55)°C
Installation	Surface Mount
Dimension (mm)	210 x 150 x 23(mm)
Outdoor Camera	Model No - CTHCC7E
Min. Illumination	0.1LUX
Lens	3.6 mm 92° angle
Light Sources	6 white LEDs
Video Output	1VP-P/75Ω
Audio SNR	>25dB
Audio Distortion	<5%
Standby Current	≤60mA
Working Current	≤230mA
Operating Voltage	DC18V±10%
Operating Temperature	(-40)~70°C
Operating Humidity	0 ~100%
Installation	Surface Mount
Dimension (mm)	79 x 148 x 45(mm)

Features

Hands-free Video Door Phone to call, monitor, and release door Locks

Expandable up to 4 Indoor Monitors and 4 Outdoor Cameras

Call Transfer, Broadcasting and Intercom Facility between Indoor Monitors

Sleek and Elegant Design suitable for villas and apartments

Backlit Touch Buttons

Do Not Disturb option available. Mutes the call ringing from Outdoor Camera while only displaying the video

More than 10 melodies for ringtone selection

4 wire System, PLUG & PLAY connection, easy to install

6 White LED's on Outdoor Camera provides clear colored image at night

Connect and Operate all kinds of Electric Door locks

Vandal-proof Outdoor Camera Made of Cast-Aluminum

Backlit Name Tag and Call Button on Outdoor Camera

Available from:

