

# 80mm High-Quality Thermal Receipt Printer



## RETAIL

### Thermal Receipt Printer TP160PLUS

#### Main Features

- .Support cash drawer connection
- .Receipt printout alerting and error alarm function
- .Low noise thermal printing with 300 mm/sec speed
- .Printer authentication and software bundle
- .Built in data buffer
- .Support GB2312 and various international fonts
- .Serial or USB or Parallel port optional
- .Windows 9X, ME, 2000, 2003, XP, Vista, 7, 8 driver supported
- .Easy Operation, Easy Maintenance with direct thermal printing



### Technical Specifications

Product	TP160PLUS
Print method	Direct thermal line
Resolution	203dpi
Print width	64/72mm
Print speed	300 mm/s
Interface	USB+ETHERNET+SERIAL
Paper diameter	83mm
Line space	3.75mm(can be adjustable)
Code page	PC437/Katakana/PC850/PC860(Portuguese)/PC863/PC865/ West Europe/Greek / Hebrew/East Europe/Iran/WPC1252(ISO 8859/2/7/15)/PC866/PC852/PC858/Iranii/PC851/PC853/Page 255 /Latvian/Arabic/P1151,1251/PC737/WPC/1257/Thai Vietnam/PC862/PC1001/ (Latvian)/PC1001/ (P1151,1251) /WPC1257/PC864/(Vietnam)/(Thai)/(PC3847 ABNT) /PC3848 ABICOMP) and more
Barcode type	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/ /EAN13+2/EAN13+5/EAN8/EAN8+2/EAN8+5/CODEBAR /POSTNET/UPC-A/UPCA+2/UPCA+5/UPC-E/UPCE+2/ UPC-E+5/CPST/MSI/MSIC/PLESSEY/ITF14/QR CODE
Character size	ANK Font Font A:12x24dots Font B:9x17dots Simplified Fonts:GB2312 Traditional Chinese:24x24dots
Buffer	Data:8K bytes NV Flash:64K bytes
Power	Power supply:AC 110V/220V,50~60Hz DC 24V/2.5A Cash drawer output: DC 24V/1A
Weight	1.2Kg
Dimension	139x181x127mm(WxLxH)
Work environment	Temperature: 0~45°C, Humidity: 10~80%
Storage environment	Temperature: -10~60°C, Humidity: 10~90%
Reliability MTBF	Mechanism: >150km Autocutter:1.5 million cuts 360,000 hours

anytime  
RETAIL

